

1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE: Dry pressed ceramic tiles with water absorption $E_b > 10\%$; BIII Group, glazed (GL)

2. INTENDED USE OR USES: For internal walls in buildings and industrial facilities.

3. MANUFACTURER: CERSANIT S.A.; Al. Solidarności 36; 25-323 Kielce

4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: SYSTEM 4

5. HARMONIZED STANDARD: EN 14411:2012

6. DECLARED PERFORMANCE:

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
Reaction-to-fire performance	A1 Classified Without Testing (CWT)
Release of dangerous substances:	
- Cadmium	Max 0,07mg/dm ²
- Lead	Max 0,8mg/dm ²
- Other	NPD
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	$\geq 0,5 \text{ N/mm}^2$
- dispersion adhesives	$\geq 1 \text{ N/mm}^2$
- reaction resin adhesives	$\geq 2 \text{ N/mm}^2$
- mortar	NPD
Thermal shock resistance	Pass
Durability for:	
- internal use:	Pass
Tactility	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:

Kielce, 01.04.2020

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER


Jolanta Grzebna